ENGINE/CYLINDER CONFIGURATION	DESCRIPTION	QTY. REQ.		PART#
	Cylinder	1	Front Mount	HC5345-3
	Helm	1		HH5271-3
	Hose Kit	1	Outboard	HO51XX**
	Oil	3		HA5430
	For Extra Steer	ing Sta	Oil ation Add:	
	Helm	1	-	HH5271-3
	Fitting Kit	1	Add a	HF6007
HC5345-3 is not compatible with all engines. Refer to Application Guides on page 3-5 to page 3-10 to ensure you have the correct cylinder for your application	1000 C C C C C C C C C C C C C C C C C C	1	Station	HO51XX
			Hose	
	Oil	1	SeaStar Oil	HA5430
Non-Counter Rotating Applications up to 450HP Max. Counter Rotating Applications up to 600HP Max. Number of Turns = 5	Cylinder	1	Front Mount	HC5345-3
	Tie-Bar Kit	1		HO60XX**
	Helm	1	SeaStar*	HH5271-3
	Hose Kit	1	-	H051XX**
	Oil	3	_	HA5430
	For Extra Steering Station Add:			
	Helm	1	-	HH5271-3
	Fitting Kit	1	Add a Station	HF6007
	Hose Kit	1		H051XX**
	Oil	1	-	HA5430
DUAL ENGINE (Dual Cylinders) Non-Counter Rotating Applications up to 600HP Max. All Counter Rotating Applications up to 600HP Max Number of Turns = 6.5	Cylinder	2	Front Mount	HC5345-3
	Tie-Bar Kit	1		HO60XX**
	Helm	1	SeaStar*	HH5272-3
	Hose Kit	3		HO51XX**
	Fitting Kit	1	Tee Fittings	HF5530
	Oil	3	SeaStar	HA5430
	For Extra Steering Station Add:			
	Helm	1	- printere and the second	HH5272-3
	Fitting Kit	1	Add a Station	HF6007
	Hose Kit	1	-	H051XX**
	Oil	1	SeaStar	HA5430
OPTIONAL EQUIPMENT	Back Plate Kit (for Standard Helms)			HA5478
	20 Degree Wedge (for Standard Helms)			HA5419
	Autopilot Fitting Kit (for all -3 Helms)		HF5501	
				PA1200-2
	20 Degree Wedge (for Standard Helms) Autopilot Fitting Kit (for all -3			HF55